

TECHNICAL DATA
CONTROL & POWER

WARRANTY
1 year guarantee

PRODUCT CODE
T-150W-24VDC-IP



- @GAPLightingLtd
- GAP Lighting Ltd
- /GAPLightingLtd
- GAP Lighting Ltd



PRODUCT DESCRIPTION

All 24v products require a constant voltage power supply and should be wired in parallel. IP67 rated pre-wired power supply.

COMPATIBILITY CHART

| CODE | MAX LOAD |
|---------------|----------|
| SL-RGB-CCT | 8M |
| SL-LED14.4 | 8M |
| SL-IP6514.4 | 8M |
| SL-P28 | 4M |
| SL-MINI | 12M |
| SL-FLEXI | 15M |
| SL-24VNEON | 8M |
| DL595-RGBCCT | 3 |
| GL108 | 1-30 |
| GL108RGB/RGBW | 1-30 |

PRODUCT FEATURES

- 24v constant voltage IP67 LED driver
- 200mm cable connections
- Dual output cables for multiple connections
- For use with 24vDC LED luminaires
- For indoor or outdoor use
- Metal housing
- Mounting tabs for securing to a flat surface
- Wire direct to LED or to a T-CON5 for 24v colour changing LED
- Do not exceed 80% load of the driver
- Suitable for interior or exterior domestic, architectural, retail and commercial applications.

PRODUCT DATA

| | |
|----------------|-------------------------------|
| Model | T-150W-24VDC-IP |
| Power | 150w |
| Output Voltage | 24v constant voltage |
| Output Current | 6.25A max |
| Input | 170 - 250vAC 2 - 1.5A 50/60Hz |
| Working Temp. | -30° C - +90°C |
| Protection | IP67 |
| Dimensions | L 218mm W 60mm D 32mm |
| Weight | 725g |
| Approvals | CE ROHS |



24v LED Strip

Will power up to 8m of 14.4w/m or 4m of 28.8w/m
iFLEX / FLEX CCT / FLEX RGBW / FLEX-DMX / POWER FLEX / FLEX LINE / FLEXI / FLEX20 / FLEX65 / AQUAFLEX / MINI NEON

INSTALLATION

Please follow installation guide