

TECHNICAL DATA
CONTROL & POWER

WARRANTY
1 year guarantee

PRODUCT CODE
T-250W-12VDC



- @GAPLightingLtd
- GAP Lighting Ltd
- /GAPLightingLtd
- GAP Lighting Ltd



PRODUCT DESCRIPTION

All 12v products require a constant voltage power supply and should be wired in parallel. IP rated pre-wired power supplies are also available for 100-350w.

COMPATIBILITY CHART

CODE	MAX LOAD
SL-LED4.8	4 x 10M
SL-LED7.2	3 x 10M
SL-IP654.8	4 x 10M
SL-IP657.2	3 x 10M
SL-IP684.8	4 x 10M
SL-IP687.2	3 x 10M
GL102-RGB	1-50
GL108	1-50
GL0140-RGBW/WW	1-30
ML103-RGB	1-30

PRODUCT FEATURES

- 12v constant voltage LED driver
- Covered screw terminals
- For use with 12vDC LED luminaires
- For indoor use or within an enclosure
- Metal housing
- Dual terminals on output
- Voltage adjust screw
- Mounting tabs for securing to a flat surface
- Wire direct to LED or to a T-CON5 for 12v colour changing LED
- Do not exceed 90% load of the driver
- Suitable for interior architectural, retail and commercial applications.

PRODUCT DATA

Model	T-250W-12VDC
Power	250w
Output Voltage	12v constant voltage
Output Current	20A max
Input	100-120vAC 3.6A 200 - 240vAC 1.8A 50/60Hz
Working Temp.	=0° C - 60°C
Protection	IP20
Dimensions	L 199mm W 110mm D 50mm
Weight	740g
Approvals	CE ROHS



12v LED Strip

Will power up to 30m of 7.2w/m
or 45m of 4.8w/m
FLEX20 / FLEX65 / AQUAFLEX

INSTALLATION

Please follow installation guide