

TECHNICAL DATA  
CONTROL & POWER

WARRANTY  
1 year guarantee

PRODUCT CODE  
T-250W-24VDC-IP



- @GAPLightingLtd
- GAP Lighting Ltd
- /GAPLightingLtd
- GAP Lighting Ltd



PRODUCT DESCRIPTION

All 24v products require a constant voltage power supply and should be wired in parallel. IP67 rated pre-wired power supply.

COMPATIBILITY CHART

CODE	MAX LOAD
SL-RGB-CCT	13M
SL-LED14.4	13M
SL-IP6514.4	13
SL-P28	6M
SL-MINI	20M
SL-FLEXI	25M
SL-24VNEON	13M
DL595-RGBCCT	5
GL108	1-30
GL108RGB/RGBW	1-30

PRODUCT FEATURES

- 24v constant voltage IP67 LED driver
- 200mm cable connections
- Dual output cables for multiple connections
- For use with 24vDC LED luminaires
- For indoor or outdoor use
- Metal housing
- Mounting tabs for securing to a flat surface
- Wire direct to LED or to a T-CON5 for 24v colour changing LED
- Do not exceed 80% load of the driver
- Suitable for interior or exterior domestic, architectural, retail and commercial applications.

PRODUCT DATA

Model	T-250W-24VDC-IP
Power	250w
Output Voltage	24v constant voltage
Output Current	10.5A max
Input	185 - 250vAC 2.9 - 2.1A 50/60Hz
Working Temp.	-30° C - +90°C
Protection	IP67
Dimensions	L 228mm   W 72mm   D 32mm
Weight	900g
Approvals	CE   ROHS



24v LED Strip

Will power up to 13m of 14.4w/m or 6m of 28.8w/m  
iFLEX / FLEX CCT / FLEX RGBW / FLEX-DMX / POWER FLEX / FLEX LINE / FLEXI / FLEX20 / FLEX65 / AQUAFLEX / MINI NEON

INSTALLATION

Please follow installation guide