

TECHNICAL DATA
CONTROL & POWER

WARRANTY
1 year guarantee

PRODUCT CODE
T-250W-24VDC



- @GAPLightingLtd
- GAP Lighting Ltd
- /GAPLightingLtd
- GAP Lighting Ltd



PRODUCT DESCRIPTION

All 24v products require a constant voltage power supply and should be wired in parallel. IP rated pre-wired power supplies are also available for 100-350w.

COMPATIBILITY CHART

CODE	MAX LOAD
SL-RGB-CCT	15M
SL-LED14.4	15M
SL-IP6514.4	15M
SL-P28	8M
SL-MINI	20M
SL-FLEXI	20M
SL-24VNEON	15M
DL595-RGBCCT	5
GL108	1-100
GL108RGB/RGBW	1-100

PRODUCT FEATURES

- 24v constant voltage LED driver
- Covered screw terminals
- For use with 24vDC LED luminaires
- For indoor use or within an enclosure
- Metal housing
- Dual terminals on output
- Voltage adjust screw
- Mounting tabs for securing to a flat surface
- Wire direct to LED or to a T-CON5 for 24v colour changing LED
- Do not exceed 90% load of the driver
- Suitable for interior architectural, retail and commercial applications.

PRODUCT DATA

Model	T-250W-24VDC
Power	250w
Output Voltage	24v constant voltage
Output Current	10A max
Input	100-120vAC 3.6A 200 - 240vAC 1.8A 50/60Hz
Working Temp.	=0° C - 60°C
Protection	IP20
Dimensions	L 200mm W 110mm D 50mm
Weight	760g
Approvals	CE ROHS



24v LED Strip

Will power up to 15m of 14.4w/m or 8m of 28.8w/m
iFLEX / FLEX CCT / FLEX RGBW / FLEX-DMX / POWER FLEX / FLEX LINE / FLEXI / FLEX20 / FLEX65 / AQUAFLEX / MINI NEON

INSTALLATION

Please follow installation guide