info@gaplighting.co.uk +44 1322 620 100 www.gaplighting.co.uk

TECHNICAL DATA

CONTROL & POWER

PRODUCT CODE

T-300W-24VDC

GAP LIGHTING
SMART LED SOLUTIONS

WARRANTY

1 year guarantee

@GAPLightingLtd
GAP Lighting Ltd
/GAPLightingLtd
GAP Lighting Ltd

PRODUCT DESCRIPTION

All 24v products require a constant voltage power supply and should be wired in parallel.
IP rated pre-wired power supplies are also available for 100-350w.

COMPATIBILITY CHART

CODE	MAX LOAD
SL-RGB-CCT	19M
SL-LED14.4	20M
SL-IP6514.4	20M
SL-P28	10M
SL-MINI	30M
SL-FLEXI	35M
SL-24VNEON	20M
DL595-RGBCCT	6
GL108	1-100
GL108RGB/RGBW	1-100

PRODUCT FEATURES

24v constant voltage LED driver

Covered screw terminals

Fan assisted (according to working temperature)

For use with 24vDC LED luminaires

For indoor use or within an enclosure

Metal housing

Dual terminals on output

Voltage adjust screw

Mounting tabs for securing to a flat surface

Wire direct to LED or to a T-CON5 for 24v colour changing LED

Do not exceed 90% load of the driver

Suitable for interior architectural, retail and commercial applications.

PRODUCT DATA

Model	T-300W-24VDC
Power	300w
Output Voltage	24v constant voltage
Output Current	12.5A max
Input	100-120vAC 6.5A 200 - 240vAC 4A 50/60Hz
Working Temp.	=0° C - 60°C
Protection	IP20
Dimensions	L 215mm | W 114mm | D 48mm
Weight	800g
Approvals	CE | ROHS

24v LED Strip

Will power up to 20m of 14.4w/m
or 10m of 28.8w/m
iFLEX / FLEX CCT / FLEX RGBW / FLEX-DMX / POWER FLEX / FLEX LINE / FLEXI / FLEX20 / FLEX65 / AQUAFLEX / MINI NEON

INSTALLATION

Please follow installation guide